



All-electric feed mixer wagon

eVerti-Feed



The future is electric

- 100% electric
- 100% emission free
- Powerful, compact and manoeuvrable

Future sustainability

Better feeding with electricity



Innovative solution not only for the small-scale business

- The hydraulic unit features a powerful electric motor which enables maximum transmission of power to the hydraulic drive.
- Electrically powered IMS mixing auger
- Battery power for up to 10 t of mixed fodder

Compact design

- Individually adjustable driver's stand
- Maximum manoeuvrability and a wide range of equipment options offer great versatility.
- Designed for convenient and intuitive operation.



Technical data	eVerti-Feed 1251
Dimensions	
Width with crossover conveyor [m]	2.28
Width with one-sided/two-sided discharge gate [m]	2.38 / 2.48
Length with cross conveyor rear [m] *	5.95
Length with two discharge doors [m] *	5.76
Distance between bottom plate and floor (smallest set of tyres assumed) [m]	0.75
Dead weight	
Basic machine [kg]	ca. 5.500
Axle	
Track [mm]	1.600
Axle distance [mm]	3.130
Loading	
Usable mixing capacity [m ³]	10 / 11 / 12.5
Vehicle height depending on tyres	
30 x x11.5-14x5	2.59 / 2.77 / 2.95
10x0/75-15.3	2.61 / 2.79 / 2.97
400/60-15.5	2.70 / 2.88 / 3.06
250/70-15	2.60 / 2.78 / 2.96
435/50R19.5	2.78 / 2.96 / 3.14
Twin 8.15 - 15	2.58 / 2.79 / 2.94
Drive	
Battery power [kWh]	40

Technical modifications reserved
* with driver's cab in 45° degree position